

# FlameSpec UV-IR-F-HD

UV/IR Flame Detector



The FlameSpec UV-IR-F-HD detector offers extremely fast detection of fires and explosions, providing the extra, extremely valuable time that, in many cases, can make all the difference

## Introduction

The FlameSpec-UV-IR-F-HD flame detector provides ultra-fast response, high performance and reliable detection of a large variety of hydrocarbon fires (visible and non-visible).

The detector addresses slow growing fires as well as fast eruptions of fire using improved UV-IR technology operating in all weather and light conditions.

The detector provides a high-definition (HD) color video output of the monitored area with clear imaging of fire events and personnel at distances up to 100 ft. (30m) allowing responders to know the exact situation before entering the hazardous area.

Video and data of events are quickly stored to non-volatile memory. The recordings start one minute before detection and continue for up to four minutes, the event video can be used for post incident investigation.

## Key Benefits

- High immunity to false alarm
- Hydrocarbon flame detection, using IR spectrum in the 4.0-5.0µm range
- High sensitivity – up to 100 ft. (30m) for a 1 ft<sup>2</sup> (0.1m<sup>2</sup>) n-heptane fire.
- Ultra-fast detection within 5 milliseconds for fireballs or explosions.
- High speed (<0.5s) model [X5] available for compliance with NFPA 33.
- HD or composite video output with automatic recording of fire events.
- Data/Event logger: Alarms, faults & video as well as other relevant events are logged to non-volatile memory.
- Universal outputs, 3 and 4 wire, 4-20 mA sink / source, Fire, Auxiliary and Fault Relays. RS485 port using Modbus RTU.
- Built-in-Test (BIT) – Automatic and manual self-test of window cleanliness and overall detector operation.
- Additional dirty optics warning for preventive maintenance needs.
- HART® 7, option available - for configuration and maintenance.
- Window heater to avoid condensation and icing.
- Stainless steel tilt mount with horizontal and vertical adjustment.
- SIL 2 capable - option available.
- Detect high UV (sparks and arcs) or IR levels via auxiliary relay and 4-20mA.

# FlameSpec UV-IR-F-HD

UV/IR Flame Detector

Model: FLS-UV-IR-F-HD

## Immunity to False Alarm

False Alarm Source	Modulated		Unmodulated	
	Distance ft. (m)	Response	Distance ft. (m)	Response
Sunlight, Direct, Reflected		No Alarm		No Alarm
Incandescent frosted glass light, 300W	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Fluorescent, 70W (3x23.3W)	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Electric arc	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Arc welding	10.0 (3.0)	No Alarm	10.0 (3.0)	No Alarm
Radiation heater, 2000W	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Halogen lamp (500W) non-shielded	10.0 (3.0)	No Alarm	10.0 (3.0)	No Alarm
Halogen lamp (1000W)	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Mercury vapor lamp 160Wx3	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Exhausts	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Projector led	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Solenoid bell	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
soldering iron	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm
Electric Drill	2.0 (0.5)	No Alarm	2.0 (0.5)	No Alarm

# FlameSpec UV-IR-F-HD

UV/IR Flame Detector

Model: FLS-UV-IR-F-HD

## Response Characteristics

Fuel	Size	Sensitivity	Distance ft. (m)	Avrg Resp.Time (s)
N-Heptane	1 x 1 ft.	Extreme	98 (30)	3.2
N-Heptane	1 x 1 ft.	High	75 (23)	1.6
N-Heptane	1 x 1 ft.	Medium	49 (15)	1.4
N-Heptane	1 x 1 ft.	Low	16 (5)	0.9
Gasoline	2 x 2 ft.	Extreme	197 (60)	5.3
Gasoline	1 x 1 ft.	Extreme	98 (30)	3.4
Gasoline	1 x 1 ft.	Medium	49 (15)	2.7
Methane	32-in Plume	Extreme	59 (18)	1.6
Methane	32-in Plume	Medium	30 (9)	0.9
LPG	32-in Plume	Extreme	75 (23)	1.2
LPG	32-in Plume	High	56 (17)	1.6
LPG	32-in Plume	Medium	33 (10)	1.3
LPG	32-in Plume	Low	13 (4)	1.0
Diesel	1 x 1 ft.	Extreme	75 (23)	4.3
Diesel	1 x 1 ft.	Medium	36 (11)	1.6
JP5	1 x 1 ft.	Extreme	75 (23)	7.0
JP5	1 x 1 ft.	High	56 (17)	2.3
JP5	1 x 1 ft.	Medium	36 (11)	1.5
JP5	1 x 1 ft.	Low	16 (5)	2.6
Kerosene	1 x 1 ft.	Extreme	75 (23)	2.9
Kerosene	1 x 1 ft.	Medium	36 (11)	1.4
Methanol	1 x 1 ft.	Extreme	59 (18)	3.6
Methanol	1 x 1 ft.	Medium	30 (9)	1.3
Ethanol	1 x 1 ft.	Extreme	72 (22)	4.5
Ethanol	1 x 1 ft.	Medium	31 (9.5)	1.2
Isopropanol	1 x 1 ft.	Extreme	75 (23)	2.8
Isopropanol	1 x 1 ft.	Medium	36 (11)	1.4
Polypropylene	1 x 1 ft.	Extreme	49 (15)	1.8
Polypropylene	1 x 1 ft.	Medium	23 (7)	1.7
Paper	1 x 1 ft.	Extreme	33 (10)	2.6
Paper	1 x 1 ft.	Medium	23 (7)	2.0
Syngas (30%CH <sub>4</sub> 70%H <sub>2</sub> )	32" plume	Extreme	66 (20)	1.0
Syngas (30%CH <sub>4</sub> 70%H <sub>2</sub> )	32" plume	Medium	33 (10)	1.2

# FlameSpec-UV-IR-F-HD

UV/IR Flame Detector

Model: FLS-UV-IR-F-HD

FIRE DETECTION	<b>Detection time and distance</b>	5ms for fast burst of explosion 1.5s for 1 ft <sup>2</sup> (0.1m <sup>2</sup> ) n-heptane pan fire at 0–50 ft. (0–15m) <3s for 1 ft <sup>2</sup> (0.1m <sup>2</sup> ) n-heptane pan fire at 50–100 ft. (15–30m)
	<b>Sensitivity Range</b>	4 sensitivity ranges: Extreme, High, Medium, Low
	<b>Field of view (IR detection)</b>	90° Horizontal, 80° Vertical
	<b>Time Delay</b>	0–30 seconds
	<b>Built in Test</b>	Automatic and Manual
VIDEO FUNCTIONALITY	<b>HD Video</b>	Color HD, as standard. Near IR filtered option (X2 available on request)
	<b>Video recording of alarm event</b>	1-minute pre-event and up to 3 minutes post-event
	<b>System integration protocol</b>	ONVIF (Open Network Video Interface Forum) Profile S
ELECTRICAL SPECIFICATIONS	<b>Operating Voltage</b>	24 VDC nominal (18-32 VDC)
	<b>Current Consumption</b>	Standby: 180mA Maximum: 300mA (including window heater)
	<b>Conduit Entries</b>	2x cable and conduit entries 3/4" NPT(F) or M25x1.5
	<b>Wiring</b>	12-20AWG (2.5-0.35mm <sup>2</sup> )
OUTPUTS	<b>Relays</b>	SPST volt-free contacts rated 2A at 30 VDC 3 relays: Alarm & Auxiliary – normally open; Fault – normally closed
	<b>0-20mA (stepped) current output</b>	3 wire and 4 wire configurations (sink and source) HART® rev 7.0 (option available)
	<b>Indication</b>	Tri-color LED (Green, Yellow, Red)
	<b>Modbus</b>	RTU compatible on RS-485
	<b>Digital (for video)</b>	IP network IEEE 802.3 100Base-T
	<b>Composite video</b>	NTSC or PAL
MECHANICAL SPECIFICATIONS	<b>Size</b>	7.87 x 5.12 x 5.12" (200x130x130mm)
	<b>Weight</b>	Detector (Stainless Steel 316): 9.8 lbs. (4.4 kg) Tilt mount (Stainless Steel 316): 5.4 lbs. (2.4 kg)
ENVIRONMENTAL SPECIFICATIONS	<b>Temperature Range</b>	Operating: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
	<b>Humidity</b>	Up to 99% (RH), non-condensing
	<b>Ingress Protection</b>	IP66 & 68 (2m, 24hr); NEMA 4X & 6P
APPROVALS	<b>ATEX</b>	ATEX: II2GD Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db -55°C<Ta<75°C Ex db IICT4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db -55°C<Ta<85°C
	<b>IECEx &amp; PESO</b>	Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db -55°C<Ta<75°C Ex db IIC T4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db -55°C<Ta<85°C
	<b>FMus &amp; FMc</b>	Class I, Div. 1, Groups B, C & D; T4 -50°C≤Ta≤85°C or T5 -50°C≤Ta≤75°C Class II/III, Div. 1, Groups E, F, G; T4 -50°C≤Ta≤85°C or T5 -50°C≤Ta≤75°C Class I, Zone 1, AEx/Ex db IIC T4 Gb or Class I, Zone 1, AEx/Ex db eb IIC T4 Gb -50°C≤Ta≤85°C Class I, Zone 1, AEx/Ex db IIC T5 Gb or Class I, Zone 1, AEx/Ex db eb IIC T5 Gb -50°C≤Ta≤75°C Zone 21, AEx/Ex tb IIIC T95°C Db -50°C≤Ta≤75°C or Zone 21, AEx/Ex tb IIIC T105°C Db -50°C≤Ta≤85°C
	<b>EAC CU TR</b>	1Ex d IIC T5 Gb or 1Ex de IIC T5 Gb and Ex tb IIIC T95°C Db -55°C≤Ta≤75°C 1Ex d IIC T4 Gb or 1Ex de IIC T4 Gb and Ex tb IIIC T105°C Db -55°C Ta 85°C
	<b>Performance</b>	ANSI FM 3260 EN 54-10
	<b>Functional safety</b>	Complies toSIL2, per IEC 61508 (option available)
ACCESSORIES	<b>Stainless steel weather cover, model FLS-WCO-S02</b>	
	<b>2" &amp; 3" pole mount adapters, model FLS-PMA-S23</b>	
	<b>Airshield for areas with high airborne contamination, model FLS-ASD-S02</b>	
	<b>Paint shield / cover</b>	
WARRANTY	<b>5 Years</b>	



FIRE & GAS DETECTION  
TECHNOLOGIES INC.

Fire and Gas Detection Technologies Inc. | 4222 E. La Palma Ave. Anaheim, CA 92807 USA  
Tel: (+1) 714-671-8500 | support@fg-detection.com  
Specifications subject to change without notice.